


## UT200 series (digital clamp meter) -> UT200A Specifications



Basic functions	Range	Basic accuracy
Model		<b>UT 200A</b>
DC voltage	600V	± (1.5% +5)
AC voltage	600V	± (1.0% +3)
Effective value of sine wave		40Hz ~ 400Hz
AC Current	2A / 20A / 200A	± (1.5% +5)
RMS sine wave		50Hz ~ 60Hz
Resistance	20k Ω	± (1.0% +4)
<b>Special Features</b>		
Range	Manual	√
Diode test		√
Continuity		√
Buzzer		√
Data Retention		√
Backlight	White	√
Switch mode	Key way	√
Low Voltage Display	About ≤ 7.5V	√
Input impedance	≥ 10M Ω	√
Maximum display	1999	√
Polarity measurement	Automatic	√
Measurement speed	2 to 3 times / second	√
Clamp head opening size	28mm	√
Wire size measured	Maximum 26mm (Diameter)	√
<b>Describes the main features of</b>		
Light	Weight only 230g Easy to carry.	
Small	Machine size is only 208 × 76 × 30mm Be applied to a small space.	
Structure	Fine jaw design, makes the measurement repeatability is good.	
Backlight	White backlight design makes the instrument the application environment / situation is more extensive.	
Function deployment	Electrical design for users, especially for the daily inspection of equipment / maintenance.	
<b>General Characteristics</b>		
Power	6F 22 9V	
LCD size	35.6 × 18mm	
Body Color	Red + Gray	
Standard accessories	Table pen, battery, cloth	
Standard Packaging	Box, manual, warranty card	
Standard Packing	40	
Standard Packaging Size	540 × 495 × 335mm	
Standard Gross Weight	About 23kg	

\* **Require additional charges**

Above product improvement specifications may change without notice.



# SUCONEL